



Rental Industry Standard

4 - Light 6Kw 30ft Tower
LIGHT TOWERS

KUBOTA-D1105BG

WATER COOLED DIESEL ENGINES

MODEL#

BTK64MH-30'-1000W

PRODUCT NAME

KUBOTA 4-Light 30' Light Tower

SPECIFICATIONS

4-1000 Watt Metal Halide Floodlights * Water Cooled Diesel Engine w/Safety Shutdowns
6kw Gen-set - 120/240 Volt, 1ph - 60hz * 30ft Tower 360 Rotates
30 Gallon fuel/60hr * Trailer Mounted * DOT Towing Package



STANDAR FEATURES

4 - 1000 Watt Metal Halide Floodlights with a Nema 4 reflector beam pattern, 98*H x98*V. High impact resistant glass lens, rubber gasketed to seal lens into reflector housing making fixture weather proof for use outdoors. Each Fixture can be individual adjusted both horizontal and vertical allowing operator to set fixture to target site. Water tite Fixture plugs that when connected are rated for full Water Proof operating conditions. Retractable Tower cord that when retracted fits within a metal protective sleeve for storage. 30 foot manual telescoping tower capable of rotating 360 degrees from ground level. Tower section are hot-dipped galvanized, rust proof. Full Gen-set Enclosure, side doors with hold back. Protects Engine-Generator, ballast and control panel, battery and 30 gallon fuel tank- 60hr service. Control Panels equipped with key start/stop, preheat fuel buttom, 12 volt fuel pump, hourmeter 1-20a/120v GFCI duplex, 1-20a, 125/250v Twist lock.

INDUSTRIAL UNITS PAINTED - WHITE

SCOPE OF DESIGN: Model# BTK64MH-30'-10002 Light Tower has been an Industry Standard for over 25 Years. 4-1000 watt Metal Halide Floodlights mounted on a 30 foot telescoping, 360 rotating, manual winched tower. Floodlights are powered by a Kubota Water Cooled diesel Engine equipped with low oil and high water temp. shutdown. 6000 watt Generator, 120/240v, 1ph, 60hz. Floodlight control panel with 1 - 20amp, 120v GFCI duplex and 1 - 20amp, 240v Receptacle. Key switch start/stop, hour meter, 12v fuel pump primer, pre-heat fuel system. 30 gallon / 60 hour fuel tank. Trailer mounted with DOT approved towing package. 2" Coupler Standard

DIMENSIONS: 12.6ft L x 4.6ft W x 6.6ft T

WEIGHT: 1780 LBS