



120 Volt Lighting
Class 1 - Division 2
LED FLOODLIGHT
HAZARDOUS LOCATION

FLOODLIGHTS

MODEL#
RNT: D2-TL150LED-HL 120 V

PRODUCT NAME
LED Hazardous Location Floodlights

SPECIFICATIONS

150 Watt LED * Rated Class 1 Division 2, Grp: CD
 120 Volt - 60hz

UL CERTIFIED FIXTURE/ELECTRICAL

Applications: Offshore-Marine* Environmental Containment* Industrial-Oilfield
 General Purpose Division 2 Hazardous Location Task Light

150 Watt LED will be equal to 400 Watt Metal Halide Light Performance



IMPORTANT NOTICE: This Product is not for abusive use.

Power Cord Length: 10 foot
 20,000 Sq. Ft. Illumination - 100ft Projections

Scope of Design: ONE 150 watt LED Division 2 floodlight designed for Hazardous Location Areas.
 Comes standard with a 10ft power cord with a 5-15 Explosion Proof rated plug-Division 1 Rated. Floodlights assembly mounts to an aluminum tripod stand that can be adjusted up to 7 feet.
 Tripod is shown with 10" foot pads for added stability. Tripod can be equipped with two 10" wheels for mobility.

WARNING: This product is not designed for abusive handling

DIMENSIONS: 5.5FT T X 5.0FT W

WEIGHT: 60 LBS