



25KVA-LIGHT TOWER
480 VOLT TO 120/240 VOLT
TRANSFORMER GFI SUBSTATION
TEMP POWER ELECTRICAL DISTRIBUTION

120 Volt Receptacles

MODEL#
TDS25/6C/480V - 120V Light Tower

RENTAL RATES
MONTH: \$600.00 DAY: \$20.00

SPECIFICATIONS

Six - 20amp -120 Volt GFCI Duplex * Rated for "OUTDOOR USE"
 25kva * 480 Volt to 120/240 Volt - 1ph - 60hz Encapsulated Transformer
 4 - 1000 Watt Metal Halide Floodlights * 20ft Telescoping Tower 360 Rotate

UL CERTIFIED 1640 - "Job-site Distribution"

Applications: Electrical Tooling * Temporary Lighting

NOTE: These Units can be supplied with 10kva to 50kva Transformers



FORKLIFT AND CENTER POINT LIFT

SCOPE OF DESIGN: 25Kva Encapsulated Transformer rated 480 Volt - 120/240 Volt, 1ph, 60hz. With 3ph line power 25ft power cord to a 480v, 3ph, 4wire 100amp fused disconnect main ON/OFF switch. 480 volt 1ph/3wire is feed to primary side of transformer, 120/240 Volt 1ph secondary is connected to 125amp, Main Breaker, Load Center rated 120/240 Volt, BONDED. Load Center can hold up to 12 Breakers. A combination of single or double pole breakers can be installed. Eletrical components assembled within a metal cage with fork lift and center point lift.

4-1000 Watt Metal Halide Floodlights 20ft Telescoping 360 Rotatin Tower

NOTE: This System is UL 1640 Certified for Job-site Portable Electrical Distribution

DIMENSIONS: 48"W X 48"D x 84"H

WEIGHT: 475 lbs