



25KVA
480 VOLT TO 120/240 VOLT
TRANSFORMER GFI SUBSTATION
 TEMP POWER ELECTRICAL DISTRIBUTION

120 Volt Receptacles

MODEL#
 TDS25/10C/480V - 120/240V SKID

RENTAL PRODUCT
 25KVA- 480V- 120V GFI SKID MOUNT

SPECIFICATIONS

10 - 20amp -120 Volt GFCI Duplexs * Rated for "OUTDOOR USE"
 25kva * 480 Volt to 120/240 Volt - 1ph - 60hz Encapsulated Transformer
UL CERTIFIED 1640 - "Job-site Distribution"
 Applications: Electrical Tooling * Temporary Lighting
 Forklift Pockets - Single Point Lift

NOTE: These Units can be supplied with 10kva to 50kva Transformers



FORKLIFT POCKETS AND CENTER POINT LIFT

SCOPE OF DESIGN: 25kva Encapsulated Transformer rated 480 Volt - 120/240 Volt, 1ph, 60hz. With 3ph line power connected to 480v, 3ph, 4wire. 60amp fused disconnect main ON/OFF switch. 480 volt 1ph/3wire is feed to primary side of transformer, 120/240 Volt 1ph secondary is connected to 125amp, Main Breaker, Load Center rated 120/240 Volt, BONDED. Load Center can hold up to 12 Breakers. A combination of single or double pole breakers can be installed. Eletrical components assembled within a metal cage with fork lift pockets.

NOTE: Units are available with 30kva - 45kva and 75kva Transformers

NOTE: This System is UL 1640 Certified for Job-site Portable Electrical Distribution

DIMENSIONS: 48"W x 40"D X 40" T

WEIGHT: 300 LBS