



40' Portable Mini Stadium Light Tower

- 40' 8X1000W Metal Halide Floodlights
- 15 Acres at 750' Light Projection

Product Specifications

Model# BMUX8MH-40-1000W



- **8 x 1000 Watt Metal Halide** floodlights mounted on a 40' telescoping tower as shown in the photo on the left. Light fixtures can be rotated up to 360 degrees. These floodlights are protected with a high impact resistant glass lens and are weatherproof rated.
- **Light Performance:** Total lumen output per system is 880,000 lumens. Fixtures can be adjusted in any direction horizontal or vertical. 360 degree rotating light head fixture is optional.
- **Tower:** 1500lb electronic winch telescoping tower with safety features included to prevent operator error while in use. High wind speed monitor will lower the tower at wind loads of 45mph.
- **Generator:** This 40' light tower comes equipped with a 25kva, 120/240 Volt or 480v, 1ph, 60hz generator. This gen-set is a water cooled diesel engine equipped with safety shutdown features. Auto start and stop feature is optional upon request.
- **Fuel Tank:** 42 gallon tank with a run-time of 48 hours.
- **Control Panel:** 1 - 20amp, 120v GFCI duplex and 1 - 50amp, 125/250v RV receptacle, key switch start/stop, hour meter, and tower controls.
- **Trailer:** 12.6ft long x 4.6ft wide x 6.6ft tall. Trailer comes equipped with four stabilizing jacks for leveling, 3" hitch ring, and is DOT approved for towing.
- **Weight:** 2300lb total operating weight.
- **Wind Speed Loads:** 60mph at 40ft.

- Optional Auto Start/Stop Timers Available



LEADERS IN THE PORTABLE LIGHT TOWER INDUSTRY



Model # BMUX8MH-40-1000W

Brief Specifications

40' Mini Stadium Light Tower
Electric or Diesel Powered

Floodlighting

Lamp Type	Metal Halide
Height	40 Foot
Op. Voltage	120/240v-1ph
# Fixtures	8
Lamp	1000w
Total Watts	8,000
Total Lumens	880,000
Delivered Lumens	680,000
Light Projection	750 Feet
Total Area	15 Acres

Diesel Gen-set

Engine	Isuzu Diesel, Water Cooled
# Cylinders	4
Speed	1800 RPM
Fuel Capacity	41.7 Gallons
Fuel Consumption	1.25 Gallons Per Hour
Run Time	30 Hours
Generator	25kVA Multiquip
Wattage	20kW
Voltage	208Y/120V
Phase	3PH/1PH
Sound Level	65 Decibels

Telescoping Tower

Height
Operation Method
Tower Safety Features

Optional Features

40 Foot
Electric Push-Button
4 Way Limit Switch System
Current Limit Winch Override Protection
Protective Cages Eliminate Cable Pinch Points
Wind Monitor Auto-Lowers Tower In High Winds
Auto Start & Stop Timers Available

