



(10) I-Link Explosion Proof String Lights

12V LED Class 1 Div 1 Linkable String Light System

• Suitable For Wet Locations

• Class 1 Div 1

• Lightweight Design

• IP66



Model # IL10EXP-12V

Specifications

- Class I, Division I, Groups B, C, & D
- IP66 Suitable for Wet Locations
- Meets compliance with OSHA requirements for portable lighting in wet or conductive locations in confined spaces (1926.405(a)(2)(ii)(G)).

Voltage	12V
Watts (Each)	6.5
Total Watts	65
Lumens (Each)	734 Per Lamp
Total Lumens	7340
Cord Length	100' (Power Cord)
Operating Temperature	-58°F to 140°F
CCT - Light Color	5000k
Weight	25lbs - Total System
Dimensions	H 2.6" , W 3.4" , D 2.4"
12' Spacing	Custom Spacing Lengths Available

Universal Applications



The portable hazardous location proof lighting kit is specifically designed for illuminating confined spaces where flammable gases, vapors, liquids and dusts may be present. 12V AC string light stands out from other hazardous location lighting by combining the efficiency and performance of LED technology with robust design and construction. Lighting system includes an emergency backup battery.

Additional Mounting Options Available



Single Hook



Handle Hook



Magnetic



5 Light Option