# 39W LED Explosion Proof
## 120 Volt LED Floodlighting

- UL-844-Suitable For Hazardous Locations
- NEMA 4X
- Rated For Wet Locations

** Shown on scaffold mount #SM-AL*

## Model # FS39LED-EXP-120V Specifications

- Class I, Division I, Groups C and D
- Class I, Division 2, Groups A, B, C and D
- Class 2, Division 1 & 2, Groups F, and G
- Class 3, Division 1 & 2

| | |
|---|---|
| Voltage | 120V |
| Watts | 39 |
| Total Lumens | 2,540 |
| Cord Length | 50' |
| Operating Temperature | -20°C to +40°C |
| CCT - Light Color | 5400-5600k |
| Weight | 25lbs |
| Dimensions | H 11.1" , W 9.5" , L 12.1" |

## Universal Applications

Refineries, Petrochemical, Steel Mills, Grain Silos, Sugar Mills, Offshore Marine, and other Hazardous Dust Location facilities.

## Also Available In The Following Mounting Options

Floor Stand
#FS-AL

Spider Magnet
#SMB-AL

Quadpod
#QP8-AL

Spring Mount
#VRSM-AL

Cart Mount
#CM-AL

Pipe Clamp
#PC-AL

Phone: (866) 442-0260 | Email: rentals@bossltr.com | bossltr.com