



15kva GFCI Distribution Substation

Certified UL1640 Power Distribution
(TDS-GFCI) Temporary Power Distribution
Custom Built to Client Site Specifications

- UL Listed
- Portable
- Special Design & Assembly
- UL Certified

Emergency Response Power "Man-Cart"



5 x 20a 120v 5-20R GFCI Duplex
1 x 30a 120/240v Twist Lock receptacle

Reduced size to fit through door ways
when power is required inside of Hotels,
Office Buildings, and Restaurants for
emergency 120v GFCI outlets.

Model # TDS15-6C/480V

Scope of Design

- 100' Power Cord w/open end wire-hard connection.
- 30 amp Main Fused Disconnect / 35a - 600v Fuses.
- Load side of Disconnect connected through tubing to the line side 480v, 1ph encapsulated WP.
- 15kva Transformer, 480v to 120/240v, 1ph, 4 wire.
- Secondary of Transformer is connected to line side.
- 125a Load Center with Main Breaker, 1ph,N,Grd.
- Installed 5 X 20A, 1P, and 1 X 30A, 2P breakers.
- Load Center mounted within a Nema 4 enclosure.
- Duplexs mounted down each side of box.
- 5 x 20amp Duplex GFCI (UL-WR MARKED) 5-20R.
- 6 x " In-use " required receptacle covers.
- 1 x 30a, 120/240v Receptacle.

Shipping Information

- TDS product can be moved by one man with the help of dolly cart incorporated into product.
- Dimensions: T 40" X W32" X D36"
- Weight: 110lbs

This (TDS) Midget man is designed to produce strong stable voltage power 120v GFCI when dryers and blowers are used during emergency clean up for disaster relief responders.

15kva Temporary GFCI Distribution Station - Dolly Mounted

This specific design is for use on all hard surface areas: Asphalt, Concrete, Shell-Rock. Trade Task usage that would include: Electrical, Carpentry, Pipefitter, Valve Assemble, Outside Tank & Vessel Work Areas, and Inside Plant Battery Units.

NOTE: These types of dolly mounted TDS products are available 10kva thru 25kva.

Phone: (866) 442-0260 | Email: rentals@bossltr.com | bossltr.com