



25kva GFCI Distribution Substation

Certified UL1640 Power Distribution
(TDS-GFCI) Temporary Power Distribution
Custom Built to Client Site Specifications

- UL Listed
- Portable
- Special Design & Assembly
- UL Certified



10 x 20a 120v 5-20R GFCI Duplex

Model # TDS25-10C-480V

Scope of Design

- 25' Power Cord w/open end wire -hard connection.
- 60 amp Main Fused Disconnect /45a - 600v Fuses.
- Load side of Disconnect connected through tubing to the line side 480v, 1ph to Encapsulated WP.
- 25kva Transformer, 480v to 120/240v, 1ph, 4 wire.
- Secondary of Transformer is connected to line side.
- 125a Load Center with Main Breaker, 1ph,N,Grd.
- Installed 10 X 20A, 1P, Circuit Breakers.
- Load Center mounted within a Nema 4 enclosure.
- 5 x 20a Duplexs mounted down each side of box.
- 10 x 20amp Duplex GFCI (UL-WR MARKED) 5-20R.
- 10 x " In-use " required receptacle covers.

Shipping Information

- TDS product can be moved by means of single point lifting eye or by two wheel cart design.
- Dimensions: T 48" X W48" X D48'
- Weight: 375lbs

This (TDS) is the Temp Power Industry most popular RENTAL ITEM for industrial turnarounds Supplies 20 x 120v GFCI plug ins.

25kva Temporary GFCI Distribution Station - Cart Mounted

This specific design is for use on all hard surface areas: Asphalt, Concrete, Shell-Rock. Trade Task usage that would include: Electrical, Carpentry, Pipefitter, Valve Assemble, Outside Tank & Vessel Work Areas, and Inside Plant Battery Units.

NOTE: These types of cart mounted TDS products are available 10kva thru 45kva.

Phone: (866) 442-0260 | Email: rentals@bossltr.com | bossltr.com