



120W LED Hazardous Light

120V LED Floodlighting

- NEMA 4X
- Intelligent Battery Backup
- IP66
- Lightweight
- Suitable for Wet Locations



* Shown on magnet mount #MM-AL

Model Number # FS120D2-LED-120V Specifications

- Class I, Division 2, Groups A, B, C, D
- Class II, Divisions 1 & 2, Groups E, F, G
- Class III, Divisions 1 & 2
- Zone 2 & Zone 21
- Ex ec op is IIC T5/T4 Gc
- Ex op is TB IIIC T95°C Db

Voltage	120V
Watts	120
Total Lumens	15,140
Cord Length	100'
Operating Temperature	-50°C to +65°C
CCT - Light Color	5000k
Weight	25lbs
Dimensions	H 14.2" , W 6.8" , L 18.6"

Universal Applications

Refineries, Petrochemical, Steel Mills, Grain Silos, Sugar Mills, Offshore Marine, Sewage Treatment Plants, and other Hazardous Location facilities.

Also Available In The Following Mounting Options



Scaffold Mount
#SM-AL



Spider Magnet
#SMB-AL



Floor Stand
#FS-AL



Pipe Clamp
#PC4-AL



Cart Mount
#CM-AL



Quadpod
#QP8-AL