



# 120W LED Hazardous Light

## 120V LED Floodlighting

- NEMA 4X
- Intelligent Battery Backup
- IP66
- Lightweight
- Suitable for Wet Locations



\* Shown on spider magnet mount #SMB-AL



### Model Number # FS120D2-LED-120V Specifications

- Class I, Division 2, Groups A, B, C, D
- Class II, Divisions 1 & 2, Groups E, F, G
- Class III, Divisions 1 & 2
- Zone 2 & Zone 21
- Ex ec op is IIC T5/T4 Gc
- Ex op is TB IIIC T95°C Db

Voltage	120V
Watts	120
Total Lumens	15,140
Cord Length	100'
Operating Temperature	-50°C to +65°C
CCT - Light Color	5000k
Weight	25lbs
Dimensions	H 14.2" , W 6.8" , L 18.6"

### Universal Applications

Refineries, Petrochemical, Steel Mills, Grain Silos, Sugar Mills, Offshore Marine, Sewage Treatment Plants, and other Hazardous Location facilities.

### Also Available In The Following Mounting Options



Scaffold Mount  
#SM-AL



Floor Stand  
#FS-AL



Pipe Clamp  
#PC4-AL



Cart Mount  
#CM-AL



Quadpod  
#QP8-AL



Magnet Mount  
#MM-AL